



Product Overview

100-011-BK Excel Cat6 UTP Unscreened Keystone Jack IDC Punch down Black, available as part of our range of excel Cat6 keystone jacks for RJ45 network connections. Suitable for mounting in a range of housings from patch panels, faceplates and shutters, to floor boxes and work area distribution enclosures.

The socket itself is housed in a high quality ABS plastic housing which opens at the rear to reveal the IDC termination points.

Product Specifications

| Feature | Values |
|---------------------------|-----------|
| Model | Jack |
| Type of connector | RJ45 8(8) |
| Category | 6 |
| Connection type | 110 |
| Requires termination tool | Yes |
| Suitable for round cable | Yes |
| Suitable for solid core | Yes |
| Colour | Black |
| AWG-range | 2226 |




Additional specifications

| Features | Values |
|---------------------------------|--|
| Width | 16.5mm |
| Depth | 30.9mm |
| Height | 19.2mm |
| Housing | ABS High-Impact |
| RJ45 Contacts | Nickel plated phosphor bronze alloy with 50 micro-inch Gold plating |
| IDC Contacts | Tin plated phosphor bronze alloy |
| RJ45 Life | Minimum 750 insertions |
| Contact force | 100 grams with FCC compliant RJ-45 plug |
| Plug retention | 48.9 N |
| Suitable impact tool | 110 style punch down tool |
| Storage temprature | -40 to +70°C |
| Operating temprature | -10 to +60°C |
| Relative humidity (Operational) | 10% to 90% RH |









Bottom View

Product drawing





Wire Cap






Included accessories

| Accessories | Quantity |
|-----------------|----------|
| Nylon cable tie | 1 |
| Wiring cap | 1 |

Standards

| Applicable standard | Detail |
|----------------------|--|
| RoHS | Compliant to the Restriction of Hazardous Substances |
| ISO/IEC 11801-1:2017 | Information technology - Generic cabling for customer premises: Part 1 General Requirements |
| EN 50173-1:2018 | Information technology. Generic cabling systems - General requirements |
| ANSI/TIA 568-2.D | Balanced Twisted-Pair Telecommunications Cabling and Components Standards |
| UL-94-V-0 | Burning stops within 10 seconds after two applications of ten seconds each of a flame to a test bar. NO flaming drips are allowed. |
| WFD | Compliant to Waste Framework Directive |





Compliant - Does Not Contain Substances of Concern in Products

Part Number Table

SCIP

| Part Number | Description |
|---------------|---|
| 100-011 | Excel Cat6 UTP Unscreened Keystone Jack IDC Punch Down White |
| 100-011-24 | Excel Cat6 UTP Unscreened Keystone Jack IDC Punch Down White (Box 24) |
| 100-011-BK | Excel Cat6 UTP Unscreened Keystone Jack IDC Punch Down Black |
| 100-011-BK-24 | Excel Cat6 UTP Unscreened Keystone Jack IDC Punch Down Black (Box 24) |
| 100-011-BU | Excel Cat6 UTP Unscreened Keystone Jack IDC Punch Down Blue |
| 100-011-GN | Excel Cat6 UTP Unscreened Keystone Jack IDC Punch Down Green |
| 100-011-RD | Excel Cat6 UTP Unscreened Keystone Jack IDC Punch Down Red |

Excel is a world class premium performing end to end infrastructure solution designed, Manufactured, supported and delivered without compromise.



Contact us at sales@excel-networking.com

E&OE. Excel is a registered trade name of Mayflex Holdings Ltd.