# Excel Solid Cat5e Cable U/UTP LSOH Euroclass Dca 305m Box Blue

Item Code: 100-062





### **Product Overview**

Excel solid Cat5e ethernet cable U/UTP LSOH CPR Euroclass Dca are manufactured and tested to ISO 11801, EN 50173 and ANSI/TIA-568-C Cat 5e specifications, 305m boxes. Each cable consists of 8 colour coded solid copper conductors twisted together to form four pairs.

The whole cable is produced in a LSOH sheath which is metre marked and labelled with part code and DoP information.

### **Product Specifications**

| Feature                       | Values          |
|-------------------------------|-----------------|
| Conductor surface             | Bare            |
| AWG size                      | 24              |
| Conductor category            | Class 1 = solid |
| Total number of cores         | 8               |
| Stranding element             | Pairs           |
| Specification core insulation | PE              |
| Core identification           | Colour          |
| Overall screening             | None            |
| Conductor screening           | None            |
| Outer sheath material         | Copolymer       |


# Excel Solid Cat5e Cable U/UTP LSOH Euroclass Dca 305m Box Blue


Item Code: 100-062



| Outer sheath colour   | Blue   |
|---|--|
| Reaction-to-fire class according to EN 13501-6                | Dca  |
| Smoke development class according to EN 13501-6               | s2   |
| Euro class flaming droplets/particles according to EN 13501-6 | d2   |
| Euro class acidity according to EN 13501-6                    | a2   |
| Halogen free (acc. EN 60754-1/2)                              | Yes  |
| Flame retardant   | In accordance with EN 60332-1-2 and EN 50399 |
| Low smoke (acc. BS EN 61034-2)                                | Yes  |
| Outer diameter approx.  | 5.2 mm                                       |
| Operating Temperature Range                                   | -2060 °C                                     |
| Category  | 5E   |
| NVP value   | 70 %   |

# **Cross-section diagram**





# **Cable specifications**

| Features                | Values       |
|-------------------------|--------------|
| Dielectric strength     | 2.5kV for 2s |
| Maximum pulling load    | 60N/6.1KgF   |
| MBR during installation | 8x cable OD  |
| MBR installed           | 4x cable OD  |



Item Code: 100-062

### Standards

| Applicable standard           | Subject   |
|-------------------------------|---|
| ISO/IEC 11801-1:2017          | Information technology - Generic cabling for customer premises: Part 1 General Requirements   |
| IEC 61156-5:2020              | Multicore and symmetrical pair/quad cables for digital<br>communications - Part 5: Symmetrical pair/quad cables<br>with transmission characteristics up to 1 000 MHz -<br>Horizontal floor wiring - Sectional specification |
| EN 50173-1:2018               | Information technology. Generic cabling systems -<br>General requirements   |
| EN 50173-2:2018               | Information technology. Generic cabling systems - Office premises   |
| BS EN 50288-3-1:2013          | Multi-element metallic cables used in analogue and digital<br>communication and control. Sectional specification for<br>unscreened cables characterised up to 250 MHz   |
| EN 50399:2011+A1:2016         | Common test methods for cables under fire conditions.<br>Heat release and smoke production measurement on<br>cables during flame spread test. Test apparatus,<br>procedures, results  |
| IEC 60332-1-2:2004 + A12:2020 | Tests on electric and optical fibre cables under fire conditions. Test for vertical flame propagation for a single insulated wire or cable. Procedure for 1 kW pre-mixed flame  |
| ANSI/TIA 568-D:2015           | Balanced Twisted-Pair Telecommunications Cabling and Components Standards   |
| IEC 60754-2:2014              | Test on gases evolved during combustion of materials from cables - Part 2: Determination of acidity (by pH measurement) and conductivity  |
| IEC 61034-2:2005+A2:2020      | Measurement of smoke density of cables burning under defined conditions – Part 2: Test procedure and requirements   |
| EN 50575:2014 + A1:2016       | Power, control and communication cables — Cables for general applications in construction works subject to reaction to fire requirements  |
| RoHS                          | Compliant to the Restriction of Hazardous Substances  |
| WFD                           | Compliant to Waste Framework Directive  |
| SCIP                          | Compliant - Does Not Contain Substances of Concern in Products  |



## **Part Number Table**

| Part Number | Description  |
|-------------|--|
| 100-057     | Excel Solid Cat5e Cable U/UTP LSOH Euroclass Dca 305m Box Orange |
| 100-059     | Excel Solid Cat5e Cable U/UTP PVC Euroclass Eca 500m Reel Grey   |
| 100-060     | Excel Solid Cat5e Cable U/UTP LSOH Euroclass Dca 305m Box White  |
| 100-060-100 | Excel Solid Cat5e Cable U/UTP LSOH Euroclass Dca 100m Box White  |
| 100-061     | Excel Solid Cat5e Cable U/UTP LSOH Euroclass Dca 305m Box Red    |
| 100-062     | Excel Solid Cat5e Cable U/UTP LSOH Euroclass Dca 305m Box Blue   |
| 100-063     | Excel Solid Cat5e Cable U/UTP LSOH Euroclass Dca 305m Box Green  |
| 100-064     | Excel Solid Cat5e Cable U/UTP LSOH Euroclass Dca 305m Box Yellow |
| 100-066     | Excel Solid Cat5e Cable U/UTP LSOH Euroclass Dca 305m Box Violet |
| 100-102     | Excel Dual Cat5e Cable U/UTP LSOH Euroclass Eca 500m Reel White  |

Excel is a world class premium performing end to end infrastructure solution designed, Manufactured, supported and delivered without compromise.



Contact us at sales@excel-networking.com

E&OE. Excel is a registered trade name of Mayflex Holdings Ltd.