## Excel Cat5e 24 Port Screened Patch Panel 1U LSA Punch Down Black

Item Code: 100-736









| X Screened                               |
|--|
| X Choice of port density                 |
| X Supports Gigabit Ethernet              |
| X Cage nuts and mini cable ties included |
| X LSA Style Termination Blocks           |
| X T568A/B Wiring Configuration           |

#### **Product Overview**

Excel Category 5e Screened Patch Panels comply with the current standards for enhanced Category 5. Ease of installation is assured with built in rear cable management at a 90° angle to the panel facia.

### **Product Specifications**

| Feature                   | Values           |
|---------------------------|------------------|
| Number of ports - loaded  | 24               |
| Type of connector         | RJ45 8(8)        |
| Shielded                  | Yes              |
| Category                  | 5E               |
| Connection type           | LSA              |
| Number of rack units (RU) | 1                |
| Colour                    | Black            |
| Mounting method           | 19 inch mounting |
| Height                    | 44 mm            |
| Width                     | 480 mm           |
| Depth                     | 102 mm           |

## Excel Cat5e 24 Port Screened Patch Panel 1U LSA Punch Down Black


Item Code: 100-736



## **Additional specifications**

| Features                         | Values  |
|----------------------------------|---|
| Wiring Specification             | T568A/T568B   |
| RJ45 Jack Min life expectancy    | 750 insertions  |
| RJ45 Jack contact                | 50 microinch gold over 100 microinch nickel undercoat |
| IDC Contacts Max life expectancy | 200 terminations                                      |
| Contact compatibility            | 22 to 24 AWG  |
| Operating Temperature Range      | -10°C to 60°C   |
| Storage Temperature Range        | -40°C to 68°C   |
| Relative Humidity                | 10% to 90%  |
| Panel material                   | SPCC  |
| Jack housing material            | PBT, 30% glass fiber filled                           |
| IDC material                     | phosphor bronze, tin over nickel undercoat            |

## **Product drawing**



# Excel Cat5e 24 Port Screened Patch Panel 1U LSA Punch Down Black

Item Code: 100-736



### **Standards**

| Applicable standard            | Detail   |
|--------------------------------|--|
| ISO/IEC 11801-1:2017           | Information technology - Generic cabling for customer premises: Part 1 General Requirements  |
| IEC 61156-5:2009+AMD1:2012 CSV | Multicore and symmetrical pair/quad cables for digital communications - Part 5: Symmetrical pair/quad cables with transmission characteristics up to 1 000 MHz - Horizontal floor wiring - Sectional specification |
| EN 50173-1:2018                | Information technology. Generic cabling systems -<br>General requirements  |
| EN 50173-2:2007 + A1:2010      | Information technology. Generic cabling systems - Office premises  |
| ANSI/TIA 568-2.D               | Balanced Twisted-Pair Telecommunications Cabling and Components Standards  |
| ANSI/EIA-310-E                 | Electronic Industries Association standard for horizontal spacing, vertical hole spacing, rack opening and front panel width   |
| RoHS                           | Restriction of Hazardous Substances - Compliant  |
| WFD                            | Compliant to Waste Framework Directive   |
| SCIP                           | Compliant - Does Not Contain Substances of Concern in Products   |

#### **Part Number Table**

| Part Number | Description  |
|-------------|--|
| 100-736     | Excel Cat5e 24 Port Screened Patch Panel 1U LSA Punch Down Black |

Excel is a world class premium performing end to end infrastructure solution designed, Manufactured, supported and delivered without compromise.



Contact us at sales@excel-networking.com

E&OE. Excel is a registered trade name of Mayflex Holdings Ltd.